CAD GENERATED DRAWING. DON'T CHANGE BY HAND.

REV.	ECN. NO.	APPD.





INTERFACE(FRONT VIEW)

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND			VBUS	CC1	DP1	DN1	SBU1	VBUS			GND
GND			VBUS	SBU2	DN2	DP2	CC2	VBUS			GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1

PIN ASSIGNMENT

PIN NO.	A1&B12	A4&B9	B8	A5	B7	A6	A7	B6	A8	B5	A9&B4	A12&B1
SINGAL NAME	GND	VBUS	SBU2	CC1	DN2	DP1	DN1	DP2	SBU1	CC2	VBUS	GND
PCB PAD NO.	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12







RECOMMENDED PCB LAYOUT(TOP VIEW)

THICKNESS T=1.0mm
DEFAULT TOLERANCE+/−0.05

NOTES:
1. MATERIAL: SEE "TABLE 1";
2. FINISH: SEE "TABLE 1";

3. ELECTRICAL :
   3−1.CONTACT CURRENT RATING :
   5A(VBUS PIN 1.5A/PIN),
   5A(GND PIN 1.25A/PIN MAX),0.25A/PIN(OTHER PIN).
   3−2.INSULATION RESISTANCE :
   100 MEGAOHMS MIN. AT 250VDC.
   3−3.DIEELECTRIC WITHSTANDING VOLTAGE :
   100VAC MIN.
   3−4.LOW LEVEL CONTACT RESISTANCE :
   INITIAL 40mΩ MAX.
   AFTER 50mΩ MAX.

4.MECHANICAL CHARACTERISTICS :
   4−1. MATING FORCE: 5~20N.;
   4−2. UNMATING FORCE: 8~20N(INITIAL),6~20N(AFTER 5000 CYCLES);
   4−3.DURABILITY : 5,000 MATING CYCLES.
   4−4.OPERATING TEMPERATURE :−40°C TO +80°C







TABLE 1:

NO.	PART NAME	QTY	MATERIAL	DESCRIPTION	REMARK
⑤	Shell−1	1	Stainless steel	Ni PLATING;	T=0.25mm
④	MID PLATE	1	Stainless steel		T=0.15mm
③	Terminal−B	8	铜镍硅合金	Au:3u" PLATING;	T=0.15mm
②	Terminal−A	8		Au:3u" PLATING;	T=0.15mm
①	Housing	1	HIGH TEMP	Black	

X.	±0.50	X.°	± 2°
.X	±0.30	.X°	± 1°
.XX	±0.10	.XX°	± 0.5°
.XXX	± 0.05		

UNITS mm
MAT'L
FINISH
Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF E-ZONE ELECTRONIC TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPROOUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF E-ZONE ELECTRONIC TECHNOLOGY CO., LTD

深圳市合众益华科技有限公司

PART NO. EZ−USBC−1134

TITLE: TYPE C 16Pin SMT Type

APPD: RADOM

CHKD: MARK

DR: WUJY 2020/08/18

DWG NO.: EZ−USBC−1134

SCALE	SHEET	REV.
1/1	1/2	A1

由Autodesk 教育版产品制作